

# CACTUS TECHNOLOGIES USB Flash Drive 100 Series



The **Cactus Technologies USB Flash Drive - 100 Series** is a low capacity solid state flash memory product that complies with the USB2.0 standard. Cactus UFDs provide up to 8GBs of formatted storage capacity and are designed to plug in directly into the USB-A receptacles. Cactus UFDs are designed to be used in applications which require a low capacity solid state disk that is compatible with the USB interface.

## CACTUS USB FLASH DRIVE

- **INDUSTRY STANDARD USB2.0 INTERFACE**
- **FLASH DRIVE CAPACITIES**
  - 128MB to 8GB
- **PLUGS INTO INDUSTRY STANDARD USB-A RECEPTACLES**
- **VOLTAGE SUPPORT**
  - 5.0V
- **UNIQUE ELECTRONIC SERIAL ID**
- **COMPLIANT WITH USB MASS STORAGE CLASS SPEC V1.0**
- **SUPPORTS BOOTING FROM USB DEVICE**
- **SOLID STATE DESIGN WITH NO MOVING PARTS**
- **RELIABILITY**
  - Fast Data Transfer Rates
  - High Data Reliability
  - High Shock & Vibration Tolerances
  - Wide Operating Temp Range
- **ZERO DB NOISE**
- **6.5-MILLION HOUR MTBF**
- **5-YEAR WARRANTY**



### PERFORMANCE

#### Read Data Transfer Rate

up to 33MB/sec

#### Write Data Transfer Rate

up to 26MB/sec



### RELIABILITY

- Supports Wear Leveling
- Supports ECC
- Less Than 1 Error in  $10^{14}$  Bits Read
- MTBF 6,500,000 Hours



### ENVIRONMENTAL & POWER

#### Operating Temperature Range

Standard 0°C to 70°C

Extended -45°C to +90°C



### POWER CONSUMPTION

	5.0V
Read	130mA
Write	130mA
Standby	58mA



### SHOCK & VIBRATION

Shock	3000G
Vibration	20G peak-to-peak

# CACTUS TECHNOLOGIES USB Flash Drive 100 Series



## INDUSTRIAL GRADE USB FLASH DRIVE

→ INTERFACE	Industry Standard USB2.0	
→ INTERFACE TRANSFER RATE	35MB/sec	
→ POWER REQUIREMENT	DC Input Voltage	5V ± 10%
	Standby	58mA
	Read	130mA
	Write	130mA
→ ENVIRONMENTAL SPECIFICATION	Standard Temperature	0°C to 70°C
	Extended Temperature	-45°C to +90°C
	Humidity	8-95%, non-condensing
	Acoustic Noise	0dB
	Vibration	20G peak to peak max.
	Shock	3000G max.
	Altitude	100,000 feet max.
→ RELIABILITY AND MAINTENANCE	Endurance	2,000,000 erase cycles per block
	MTBF	6,500,000 Hours
	Data Reliability	less than 1 Error in 10 <sup>14</sup> bits read
→ CARD CAPACITY	128MB to 8GB	

**Cactus Technologies Limited**  
Suite C, 15/F, Capital Trade Center  
62 Tsun Yip Street, Kwun Tong  
Kowloon, Hong Kong  
Tel: +852-2797-2277  
Email: sales@cactus-tech.com

**Cactus USA**  
3112 Windsor Road  
Suite A356  
Austin, Texas 78703  
Tel: (512) 775-0746  
Email: americas@cactus-tech.com



www.cactus-tech.com