

CACTUS TECHNOLOGIES
 2.5" Solid State Drive (SSD)
230S Pro Series



The Cactus Technologies - 230S Pro Series SSD is a high capacity solid-state flash memory product that complies with the Serial ATA 3.0 standard and is functionally compatible with a SATA hard disk drive. Cactus Technologies® -230S Pro Series SSD provide up to 640GB of formatted storage capacity and have the added features of AES256 Encryption as well as Quick Erase via a hardware jumper.

CACTUS SATA III SSD FEATURES

- INDUSTRY STANDARD 2.5" FORM FACTOR
- SSD CAPACITIES
 - 128GB to 640GB
- AES256 ENCRYPTION
- QUICK ERASE (512GB in <15 seconds)
- SUPPORTS SERIAL ATA I/II/III
1.5/3.0/6.0 GBPS TRANSFER RATE
- COMPLIANT WITH:
 - Serial ATA 3.0 Spec
 - ATA8-ACS2 Command Set
- 5.0V OPERATION
- SUPPORTS:
 - ATA SMART Feature Set
 - ATA Security Feature Set
 - SATA NCQ w/ max. 32 Queue depth
 - SATA partial and slumber modes
- RELIABILITY
 - High Data Reliability
 - High Shock & Vibration Tolerances
- SOLID STATE DESIGN
- 200K HOUR MTBF
- 2-YEAR WARRANTY



PERFORMANCE

Read Data Transfer Rate
up to 380 MB/sec
Write Data Transfer Rate
up to 400 MB/sec



RELIABILITY

- Advanced Wear Leveling
- Error Checking & Correction
- Less Than 1 Error in 10¹⁴ Bits Read



ENVIRONMENTAL & POWER

Operating Temperature Range
 Standard 0°C to 70°C
 Extended Contact Cactus



POWER CONSUMPTION

	5.0V
Read	440mA
Write	1.15A
Standby	230mA



SHOCK & VIBRATION

Shock	3,000G
Vibration	20G peak-to-peak

CACTUS TECHNOLOGIES
 2.5" Solid State Drive (SSD)
230S Pro Series



COMMERCIAL GRADE SOLID STATE DRIVE

→ INTERFACE	ANSI ATA8-ACS2 Spec; Serial ATA 3.0 Spec	
→ INTERFACE TRANSFER RATE	6.0Gb/sec	
→ POWER REQUIREMENT	DC Input Voltage	5.0V ± 10%
	Standby	230mA
	Read	440mA
	Write	1.15A
→ ENVIRONMENTAL SPECIFICATION	Standard Temperature	0°C to 70°C
	Extended Temperature	Contact Cactus
	Humidity	8-95%, non-condensing
	Acoustic Noise	0dB
	Vibration	20G peak to peak max.
	Shock	3000G max.
	Altitude	100,000 feet max.
→ RELIABILITY AND MAINTENANCE	Endurance	100,000 erase cycles per block
	MTBF	200,000 Hours
	Data Reliability	less than 1 Error in 10 ¹⁴ bits read
→ CARD CAPACITY	128GB to 640GB	

Cactus Technologies Limited
 Suite C, 15/F, Capital Trade Center
 62 Tsun Yip Street, Kwun Tong
 Kowloon, Hong Kong
 Tel: +852-2797-2277
 Email: sales@cactus-tech.com

Cactus USA
 3112 Windsor Road
 Suite A356
 Austin, Texas 78703
 Tel: (512) 775-0746
 Email: americas@cactus-tech.com



www.cactus-tech.com