## **CACTUS TECHNOLOGIES**

# 2.5" Solid State Drive (SSD) 9105 Series





The Cactus Technologies Solid State Drive (SSD) - 910S

**Series** is a high capacity solid-state flash memory product that complies with the Serial ATA 3.0 standard and is functionally compatible with a SATA hard disk drive. Cactus Technologies® -910S series SSD provide up to 640GB of formatted storage capacity.

#### CACTUS SATA III SSD FEATURES

- → INDUSTRY STANDARD 2.5" FORM FACTOR
- CARD CAPACITIES
  - 64GB to 640GB
- → SUPPORTS SATA I/II/III
  1.5/3.0/6.0 GBPS TRANSFER RATE
- → 5V OPERATION
- → SUPPORTS:
  - ATA SMART Feature Set
  - ATA Security Feature Set
  - SATA NCQ w/ max. 32 Queue depth
  - SATA partial and slumber modes
- UNIQUE ELECTRONIC DEVICE ID
- → UP TO 60K IOPS
- **→** TRACEABILITY BARCODE
- SOLID STATE DESIGN
- → RELIABILITY
  - High Data Reliability
  - High Shock & Vibration Tolerances
  - Wide Operating Temp Range
- 4-MILLION HOUR MTBF
- 5-YEAR WARRANTY



#### **PERFORMANCE**

**Read Data Transfer Rate** up to 430MB/sec

Write Data Transfer Rate up to 440MB/sec



#### **RELIABILITY**

- Industrial Wear Leveling
- Industrial Error Checking & Correction
- Less Than 1 Error in 10<sup>14</sup> Bits Read
- MTBF 4,000,000 Hours



#### **ENVIRONMENTAL & POWER**

Operating Temperature Range
Standard 0°C to 70°C
Extended -45°C to +90°C



#### **POWER CONSUMPTION**

5.0V Read 470mA Write 660mA Standby 230mA



#### **SHOCK & VIBRATION**

Shock 3,000G Vibration 20G peak-to-peak

# 2.5" Solid State Drive (SSD) 9105 Series





### INDUSTRIAL GRADE SOLID STATE DRIVE

→ INTERFACE	ANSI ATA8-ACS2 Spec; Serial ATA 3.0 Spec	
→ INTERFACE TRANSFER RATE	6.0Gb/sec	
→ POWER REQUIREMENT	DC Input Voltage	5V ± 10%
	Standby	230mA
	Read	470mA
	Write	660mA
→ ENVIRONMENTAL SPECIFICATION	Standard Temperature	0°C to 70°C
	Extended Temperature	-45°C to +90°C
	Humidity	8-95%, non-condensing
	Acoustic Noise	0dB
	Vibration	20G peak to peak max.
	Shock	3000G max.
	Altitude	100,000 feet max.
→ RELIABILITY AND MAINTENANCE	Endurance	2,000,000 erase cycles per block
	MTBF	4,000,000 Hours
	Data Reliability	less than 1 Error in 10 <sup>14</sup> bits read
→ CARD CAPACITY	64GB to 640GB	

#### **Cactus Technologies Limited**

Suite C, 15/F, Capital Trade Center 62 Tsun Yip Street, Kwun Tong Kowloon, Hong Kong Tel: +852-2797-2277

Email: sales@cactus-tech.com

#### **Cactus USA**

3112 Windsor Road
Suite A356
Austin, Texas 78703
Tel: (512) 775-0746
Email: americas@cactus-tech.com





www.cactus-tech.com